

Quote Request Form

Phone: (888) 539-1731
Email: abelgiovane@jmachillers.com
Fax: (724) 925-3202



J&M Fluidics, Inc. • 851 Tech Drive • Telford, PA 18969

Chiller Information

Company Name: _____ Date: _____
Email: _____ Contact: _____
Telephone Number: _____ Fax Number: _____

- Condensing Method: Air-Cooled or Water-Cooled
 Packaged or Split System (Air-Cooled Only)
- Ambient Air Temp: _____ °F (For Air-Cooled Units) or Entering Condenser Water Temp: _____ °F (For Water-Cooled Units)
- Fluid To Be Cooled: Water Propylene Glycol _____ %
 Ethylene Glycol _____ % Other _____
(Please Specify in Detail)
- Entering Fluid Temperature _____ °F Leaving Fluid Temperature _____ °F
- Fluid Flow Rate: _____ GPM or _____ LB / HR
- Power Requirement: Voltage _____ Phase _____ Cycle _____
- Required Capacity (BTUH): _____ • Fluid Storage Tank Model Required: Yes No

Available Options

- | | |
|---|--|
| <input type="checkbox"/> Remote Idec Touchscreen Control Panel | <input type="checkbox"/> E-Coat Condenser Coil (Coastal Protection) |
| <input type="checkbox"/> Industrial VPN Router | <input type="checkbox"/> Polyester Coated Condenser Coil (Coastal Protection) |
| <input type="checkbox"/> 5 Port Ethernet Switch | <input type="checkbox"/> Copper Fin Condenser Coil (Coastal Protection) |
| <input type="checkbox"/> 4 Year Extended Warranty On Compressor Only | <input type="checkbox"/> Semi-Hermetic Compressor |
| <input type="checkbox"/> Variable Fan Speed Control | <input type="checkbox"/> Compressor Cylinder Unloading - Semi-Hermetic Only |
| <input type="checkbox"/> ECM (Digital) Fan Motor | <input type="checkbox"/> Hot Gas Bypass Capacity Control
(Semi-Hermetic Only, Standard on Scroll Units) |
| <input type="checkbox"/> Receiver / Head Pressure Control (0°F) | <input type="checkbox"/> Special Evaporator and Piping for De-Ionized Water |
| <input type="checkbox"/> Heated Receiver / Head Pressure Control (-20°F) | <input type="checkbox"/> Tank Sight Glass |
| <input type="checkbox"/> Fused Process Pump (Stainless Steel) | <input type="checkbox"/> Tank Low Level Indicator |
| <input type="checkbox"/> Dual Fused Process Pumps w/ Manual Switchover (Stainless Steel) | <input type="checkbox"/> Process Water Pressure Gauge Set |
| <input type="checkbox"/> Dual Fused Process Pumps w/ Auto Switchover (Stainless Steel) | <input type="checkbox"/> Low Flow Bypass |
| <input type="checkbox"/> Process Pump VFD (Variable Frequency Drive) | <input type="checkbox"/> Condenser Water Regulating Valve
(Water Cooled Models Only) |
| <input type="checkbox"/> Compressor Fusing | <input type="checkbox"/> Non-Fused Disconnect |
| <input type="checkbox"/> Compressor VFD (Variable Frequency Drive) - most models | <input type="checkbox"/> Fused Disconnect |
| <input type="checkbox"/> Phase Monitor | |
| <input type="checkbox"/> 115 Service Outlet (raintight) | |
| <input type="checkbox"/> Casters - Factory Mounted | |
| <input type="checkbox"/> Factory Installed Heat Tape Freeze Protection
(For ambient temperatures only) | |