




*It's All about Building a
Better Product for Our Clients!*

J&M Fluidics, Inc.
851 Tech Drive
Telford, PA 18969
Toll-Free: (888) 539-1731
Fax: 267-203-8786

Model: PSW55D

Packaged Water-Cooled 55 Ton Chiller



STANDARD ON ALL J&M MODELS:
Pentra Microsmart, Programmable Logic Controller (PLC)
with HMI Touch Screen Display.

Standard Features:

- **ETL listed** to UL1995 & CAN/CSA C22.2 No. 236-11, 4th edition, 10/14/2011
- **Semi Hermetic compressors with crankcase heater**
- **IDEC Microprocessor controller with touch screen interface**
- **STAINLESS STEEL** brazed plate evaporator
- Shell & Tube Condensers
- Suction accumulator
- Water flow switch
- Liquid line drier, sightglass, solenoid, TEV
- 1/2" insulation on all water and refrigerant lines
- Full refrigerant charge from factory
- NEMA 3R Control Panel
- 24V control transformer
- Compressor motor contactor
- Control circuit fusing
- Galvanized framed cabinet
- **Computerized factory run test under load conditions prior to shipment**



Options:

- Fused **STAINLESS STEEL** system process pump
- Condenser water regulation valves (shipped loose)
- Water pressure gauge set
- Factory installed evaporator heat tape freeze protection thermostatically controlled
- Compressor fusing
- 4 Year extended compressor warranty
- 115 volt service outlet (rain tight)
- Fused disconnect (shipped loose)
- Phase monitor



*Easy to Use
Touch Screen Display
on ALL J&M Chiller
Models*



It's All about Building a Better Product for Our Clients!

J&M Fluidics, Inc.

851 Tech Drive
Telford, PA 18969

Toll-Free: (888) 539-1731

Fax: 267-203-8786

Model: PSW55D


Packaged Water-Cooled 55 Ton Chiller

Product Dimensional Drawing

© Property of J&M Fluidics, Inc.



Product Dimensional Drawing



Dimensional & Electrical Table (Dual Circuit)

Chiller Models	85°F Cond Water 45°F LWT	Length Inches	Width Inches	Height Inches	Power			Compressor		RLA ea.	LRA ea.	MCA	M.O.P	Chiller Fluid Conn.	Weight Pounds
					Voltage	Phase	Freq.	Qty.	HP						
PSW55DN5	750,000	112	34	54	200V	3	60Hz	2	30	155.1	650	350	500	3" FPT	2490
PSW55DP5					230V	3	60Hz			141.7	594	350	450		
PSW55DH5					460V	3	60Hz			73.7	315	175	225		
PSW55DI5					575V	3	60Hz			51.6	245	125	150		

Capacity Table (Refrigerant R407C)

Model	Compressor	LWT °F	105°F		
			TONS	KW	EER
55D	6DGNR37ME	42.0	58.5	58.8	11.94
		44.0	61.2	59.4	12.36
		45.0	62.5	59.8	12.54
		50.0	69.0	60.8	13.62

J&M FLUIDICS, INC. – PRODUCT DATA SHEET