

(Stainless Steel Tank) Standard Features:

- STAINLESS STEEL recirculation tank
- 600 gallon tank size
- 1/2" tank and fluid piping insulation
- Copper fluid piping
- Tank vent and drain connections
- Tank pressure relief valve
- Fused, **STAINLESS STEEL** evaporator recirculating pump
- Recirculation pump discharge ball valve and cleanable "Y" strainer
- Control box with pump terminal block
- Galvanized steel sheet metal cabinet

Available Options:

- Fused, STAINLESS STEEL process pump
- Dual process pump with manual changeover
- Dual process pump with auto changeover
- · Pump suction isolation valve
- Process Pump VFD Controller
- Tank fluid sight glass
- Tank liquid level indicator with dry contacts
- · Low flow by-pass valve
- Water flow meter
- Auto city water make up solenoid
- 1" tank and piping insulation in lieu of 1/2"
- · Seal-tight electrical conduit and connections
- Painted Powder Coated



J&M Fluidics. Inc.



J&M Fluidics, Inc. 851 Tech Drive Telford, PA 18969

Toll-Free: (888) 539-1731 Email: info@jmchillers.com

Model: RRT600-SS

600 Gallon Process Tank & Pump Package

Product Dimensional Drawing

© Property of J&M Fluidics, Inc.

FROM PROCESS

TO CHILLER

0

6

1 in

Ш

ACCESS PANE

LEFT SIDE VIEW


Qty (8) 1/2" Mounting Holes

II



Stainless Steel Tank & Pump

Tank Model	Length Inches	Width Inches	Height Inches	Water Conn.	Tank Capacity	Recirculation Pump	FLA 230/3O	FLA 460/3Ø	Weight Lbs.
RRT600	120	56	60	4" FPT	600 Gallons	5HP	13.7	6.5	675



ACCESS PANEL

ACCESS

40 in

I

FRONT VIEW

0

10 ln

1 1


ACCESS PANEL

- 40 in


0

10 In

1 1



TOP VIEW



RIGHT SIDE VIEW