


# Quote Request Form

Phone: (888) 539-1731

Email: [abelgiovane@jmchillers.com](mailto:abelgiovane@jmchillers.com)



J&M Fluidics, Inc. • 851 Tech Drive • Telford, PA 18969

## Chiller Information

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_  
Email: \_\_\_\_\_ Contact: \_\_\_\_\_  
Telephone Number: \_\_\_\_\_ Fax Number: \_\_\_\_\_

- Condensing Method:  Air-Cooled or  Water-Cooled  
 Packaged or  Split System (Air-Cooled Only)
- Ambient Air Temp: \_\_\_\_\_ °F (For Air-Cooled Units) or Entering Condenser Water Temp: \_\_\_\_\_ °F (For Water-Cooled Units)
- Fluid To Be Cooled:  Water  Propylene Glycol \_\_\_\_\_ %  
 Ethylene Glycol \_\_\_\_\_ %  Other \_\_\_\_\_  
*(Please Specify in Detail)*
- Entering Fluid Temperature \_\_\_\_\_ °F Leaving Fluid Temperature \_\_\_\_\_ °F
- Fluid Flow Rate: \_\_\_\_\_ GPM or \_\_\_\_\_ LB / HR
- Power Requirement: Voltage \_\_\_\_\_ Phase \_\_\_\_\_ Cycle \_\_\_\_\_ *(Choose from Drop-down)*
- Required Capacity (BTUH): \_\_\_\_\_ • Fluid Storage Tank Model Required:  Yes  No

## Available Options

- |   |  |
|---|--|
| <input type="checkbox"/> Remote Idec Touchscreen Control Panel  | <input type="checkbox"/> E-Coat Condenser Coil (Coastal Protection)  |
| <input type="checkbox"/> HMI Outdoor Cover  | <input type="checkbox"/> Flow Meter (Available for most models)  |
| <input type="checkbox"/> 5 Port Ethernet Switch   | <input type="checkbox"/> Semi-Hermetic Compressor  |
| <input type="checkbox"/> 4 Year Extended Warranty On Compressor Only                                      | <input type="checkbox"/> Compressor Cylinder Unloading - Semi-Hermetic Only                                |
| <input type="checkbox"/> Variable Fan Speed Control (Only available for 1 to 22 tons)                     | <input type="checkbox"/> Hot Gas Bypass Capacity Control<br>(Semi-Hermetic Only, Standard on Scroll Units) |
| <input type="checkbox"/> ECM (Digital) Fan Motor (Only available for 26 to 91 tons)                       | <input type="checkbox"/> Special Evaporator and Piping for De-Ionized Water                                |
| <input type="checkbox"/> Receiver / Head Pressure Control (0°F)   | <input type="checkbox"/> Tank Sight Glass  |
| <input type="checkbox"/> Heated Receiver / Head Pressure Control (-20°F)                                  | <input type="checkbox"/> Tank Low Level Indicator  |
| <input type="checkbox"/> Fused Process Pump (Stainless Steel)   | <input type="checkbox"/> Process Water Pressure Gauge Set  |
| <input type="checkbox"/> Dual Fused Process Pumps w/ Manual Switchover (Stainless Steel)                  | <input type="checkbox"/> Low Flow Bypass   |
| <input type="checkbox"/> Dual Fused Process Pumps w/ Auto Switchover (Stainless Steel)                    | <input type="checkbox"/> Condenser Water Regulating Valve<br>(Water Cooled Models Only)                    |
| <input type="checkbox"/> Process Pump VFD   | <input type="checkbox"/> Non-Fused Disconnect  |
| <input type="checkbox"/> Compressor Fusing  | <input type="checkbox"/> Fused Disconnect  |
| <input type="checkbox"/> Compressor VFD - most models   |  |
| <input type="checkbox"/> Phase Monitor  |  |
| <input type="checkbox"/> 115 Service Outlet (raintight)   |  |
| <input type="checkbox"/> Casters - Factory Mounted (Only available for 1 to 22 tons)                      |  |
| <input type="checkbox"/> Factory Installed Heat Tape Freeze Protection<br>(For ambient temperatures only) |  |