FLUIDICS

It's All about Building a Better Product for Our Clients!

J&M Fluidics, Inc.
851 Tech Drive
Telford, PA 18969
Toll-Free: (888) 539-1731
Fax: 267-203-8786

J&M FLUIDICS, INC. – PRODUCT DATA SHEET

Model: PZWT11D

Packaged Water-Cooled 11 Ton Chiller *with* Stainless Steel Tank

R454C Refrigerant

STANDARD ON ALL J&M MODELS:
Pentra Microsmart, Programmable Logic Controller (PLC) with HMI Touch Screen Display.

Standard Features:

C ETL US LISTED Intertek

- Conforms to UL 60335-2-40:2022 Ed.4
  UL 60335-1:2016 Ed.6
- CSA C22.2 # 60335-1:2016 Ed.2
- CSA C22.2 # 60335-2-40:2022 Ed.4
- Single Point Power Connection
- Pentra Microsmart, Programmable Logic Controller (PLC) with easy to use HMI touch screen display
- STAINLESS STEEL, brazed plate evaporator
- Scroll compressor with crankcase heater
- Suction Accumulator
- Liquid line drier, sight glass, solenoid
- Electronic expansion valve
- Manual high pressure cutout
- Water flow switch
- Hot Gas Bypass Capacity Control
- 24V control transformer
- Control circuit fusing
- Condenser(s): Coaxial up to PZWT22D
- Condenser(s): Shell and Tube on models larger than 22 ton
- Compressor motor contactor
- Painted - Powder Coated (Most Models), galvanized sheet metal cabinet
- 1/2" insulation on all water and refrigerant lines
- Complete refrigerant charge from factory
- Factory Performance Test prior to shipment

Tank

- STAINLESS STEEL storage tank with 1/2 inch insulation
- Fused, STAINLESS STEEL re-circulation pump for tank operation with ball valve and cleanable strainer
- Tank pressure relief valve, vent and drain hose bibs

Options:

- **VFD Compressor Control**
- **Copeland Digital Scroll Compressor**
- **Remote Idec touchscreen control panel**
- **5 Port Ethernet Switch**
- **BacNet Gateway**
- **Process Pump VFD Controller**
- 4 year extended compressor warranty
- Casters (factory mounted)
- Condenser water regulating valve
- 115 volt (rain tight) service outlet
- Non Fused Disconnect
- Phase Monitor, line voltage monitor offering protection against phase loss/reversal, unbalance and hi/lo voltage
- Compressor fusing
- Compressor Sound Cover
- Factory installed evaporator heat tape freeze protection
- Low flow by-pass valve
- Fused, STAINLESS STEEL process pump
- Dual system pump with manual changeover (some models)
- Dual system pump with auto changeover (some models)
- Pump suction isolation valve
- Water pressure gauge set
- Water Flow Meter
- Auto city water changeover panel with filter
- Tank City Water Makeup
- Stainless steel, SCH80 PVC or Polypropylene piping for deionized and reverse osmosis water systems
- Door Mounted HMI weather proof cover

Tank Options

- Storage tank sight glass
- Tank low liquid level indicator with dry contacts

© Property of J&M Fluidics, Inc.

J&M Fluidics, Inc.
851 Tech Drive
Telford, PA 18969
Toll-Free: (888) 539-1731
Fax: 267-203-8786

It's All about Building a Better Product for Our Clients!

Model: PZWT11D

Packaged Water-Cooled 11 Ton Chiller *with* Stainless Steel Tank

R454C Refrigerant

Intertek

Product Dimensional Drawing

© Property of J&M Fluidics, Inc.











Dimensional & Electrical Table (Dual Circuit)

Chiller Model	Nominal BTUH	Length Inches	Width Inches	Height Inches	Power			Compressor Qty.	RLA ea.	LRA ea.	Recirculation Pump FLA	MCA	MOP	Reservoir Gal.	Chiller Fluid Conn	Weight Pounds
					Voltage	Phase	Freq.									
PZWT11DF8	119400	75	34	70	208/230	3	60	2	20.2	156	4.66	50	70	80	1.25 "FPT	1250
PZWT11DH8					460	3	60		9.1	75	2.11	23	30			
PZWT11DI8					575	3	60		6.3	54	1.69	16	20			

Capacity Table (Refrigerant R454C)

Model	COMPRESSOR	COND(°F)	105		
		LWT (°F)	TONS	KW	EER
11D	YB40KAE	42	9.4	9.1	12.3
		44	9.8	9.2	12.8
		45	10.0	9.2	13.0
		50	10.6	9.2	13.8

1. Capacities on this chart are based on refrigerant R454C. Lower leaving water or low ambient can require the use of a glycol solution or other fluid blends. These solutions affect unit capacities. Please consult the factory on these or other special fluids.
2. KW input is for compressor(s) only.
3. EER = Energy Efficiency Ratio (BTU/watt-hour). Power inputs include compressor (s), condenser fan motor (s) and control power.

© Property of J&M Fluidics, Inc.

J&M FLUIDICS, INC. – PRODUCT DATA SHEET